



大恭化學工業股份有限公司

TAH KONG CHEMICAL INDUSTRIAL CORP.

7TH FLOOR 778, PA TE ROAD, SEC.4,

TAIPEI, REPUBLIC OF CHINA

台北市八德路四段七七八號

新矽谷大樓七樓

TEL:(02)7859081-7

TLX:25217 TKCPIGMENT

CABLE:TKCHEMIAL TAIPEI

FAX:(02)7850907

Anti-Blocking TPU Master Batch

1. **Description:** TPU is an Eco-friendly material to replace PVC. The thinner of the TPU film, the poorer processability it has. Especially at the production of TPU film, the anti-blocking master batch can improve the processability of TPU. It not only has no content of restricted material in the formulation, but also has excellent anti-blocking effect ness and dispersion. It is applicable for the production at blown film or T-Die extrusion machine.
2. **Characteristics:**
 - a. Excellent anti-blocking
 - b. Excellent transparency
 - c. No blushing after extension
 - d. Smooth touching
 - e. No influence to downstream lamination
 - f. No blooming
3. **Item Code:** TPA NC 5U423
4. **Appearance:** Pellet
5. **Recommended Dosage:** 5%
Dosage is adjustable according to specific requirement on thickness and anti-blocking.
6. **Remark:** adequate drying before using is recommended.



大恭化學工業股份有限公司

TAH KONG CHEMICAL INDUSTRIAL CORP.

7TH FLOOR 778, PA TE ROAD, SEC.4,

TAIPEI, REPUBLIC OF CHINA

台北市八德路四段七七八號

新矽谷大樓七樓

TEL:(02)7859081-7

TLX:25217 TKCPIGMENT

CABLE:TKCHEMIAL TAIPEI

FAX:(02)7850907

Slipping Agent TPU Master Batch

1. **Description:** TPU is an Eco-friendly material to replace PVC. The thinner of the TPU film, the poorer processability it has. Especially at the production of TPU film, the slipping agent master batch can improve the processability of TPU. It not only has no content of restricted material in the formulation, but also has excellent anti-blocking effect ness and dispersion. It is applicable for the production at Blown film or T-Die extrusion machine.
2. **Characteristics:**
 - g. Excellent anti-blocking
 - h. Excellent transparency
 - i. No blushing after extension
 - j. Smooth touching
 - k. No influence to downstream lamination
 - l. No blooming
3. **Item Code:** TPA NC 5U424 (Polyester TPU) 、 TPA NC 5U524 (Polyether TPU)
4. **Appearance:** Pellet
5. **Recommended Dosage:** 5%

Dosage is adjustable according to specific requirement on thickness and anti-blocking.
6. **Remark:** adequate drying before using is recomme nded.